

ADAM-6510**ADAM-6520/6522****ADAM-6521****4-Port Industrial 10 Mbps Ethernet Hub****5-Port/3-port Industrial 10/100 Mbps Ethernet Switch****5-Port Industrial 10/100 Mbps Ethernet Switch with Fiber port**

ADAM-6510 **4-Port Industrial 10 Mbps Ethernet Hub**

- **Interface:** Network: 10 Base-T standard
- **Port:** 4 x 10 Mbps, 1 x 10 Mbps uplink
- **Connector:** RJ-45
- **Compatibility:** IEEE 802.3, IEEE 802.3u
- **Surge protection (Power):** 3000 V_{DC}
- **LED:** Power, 10/100 Mbps
- **Power Requirements:** unregulated 10 to 30 V_{DC}
- **Power Consumption:** 2 W (Typical)
- **Case:** ABS with captive mounting hardware
- **Placement:** DIN-rail, Panel mounting, piggyback stack
- **Operating Temperature:** -10 to 70°C
- **Storage Temperature:** -20 to 80°C
- **Operating Humidity:** 20 to 95% (non-condensing)
- **Storage Humidity:** 0 to 95% (non-condensing)

ADAM-6520/6522 **5-Port/3-port Industrial 10/100 Mbps Ethernet Switch**

- **Interface:** Network: 10 Base-T
- **Port:** 5 x 10 Mbps (ADAM-6520), 3 x 10 Mbps (ADAM-6522)
- **Connector:** RJ-45
- **Compatibility:** IEEE 802.3, IEEE 802.3u
- **Surge protection (Power):** 3000 V_{DC}
- **LED:** Power, 10/100 Mbps
- **Power Requirements:** unregulated 10 to 30 V_{DC}
- **Power Consumption:** 2 W (Typical)
- **Case:** ABS with captive mounting hardware
- **Placement:** DIN-rail, Panel mounting, piggyback stack
- **Operating Temperature:** -10 to 70°C
- **Storage Temperature:** -20 to 80°C
- **Operating Humidity:** 20 to 95% (non-condensing)
- **Storage Humidity:** 0 to 95% (non-condensing)

ADAM-6521 **5-Port Industrial 10/100 Mbps Ethernet Switch with Fiber port**

- **Interface:** Network: 10 Base-T & 10 Base-FX standard
- **Port:** 4 x 10/100 Mbps (RJ-45), 1 x 100 Mbps (Fiber)
- **Connector:** 4 x RJ-45 & 1 x Fiber (SC type)
- **Compatibility:** IEEE 802.3, IEEE 802.3u
- **Surge protection (Power):** 3000 V_{DC}
- **LED:** Power, 10/100 Mbps
- **Transmission Distance (Fiber):** 2000 m
- **Power Requirements:** unregulated 10 to 30 V_{DC}
- **Power Consumption:** 2 W (Typical)
- **Case:** ABS with captive mounting hardware
- **Placement:** DIN-rail, Panel mounting, piggyback stack
- **Operating Temperature:** -10 to 65°C
- **Storage Temperature:** -20 to 80°C
- **Operating Humidity:** 20 to 95% (non-condensing)
- **Storage Humidity:** 0 to 95% (non-condensing)

